

ISOLATION TRANSFORMERS

SERIES

5-1200 kVA

1-25 kVA

3

PHASE

1

PHASE

Usage Areas:

- UPS Systems
- Medical Devices
- CNC Machines
- Ships and Boats
- Shipyards
- Metal Processing Plants
- Rectifier and Battery Chargers
- Industrial Machines Power Supply Units



MEDICAL



INDUSTRY



TRANSPORT



HIGHLIGHTS

- Reliable, Electrical Isolation
- Suppresses Electrical Noise
- Ensures Complete Safety of Equipment

Excellent Protection & High Level of Isolation

- An isolation transformer is the best way to establish a new neutral-ground bond, in order to correct common mode and other grounding problems.
- Isolation transformer provides excellent protection from all types of N-G disturbances (impulses, RMS voltage, and high frequency noise).



FEATURES

- Input Voltage : 230 VAC Ph+N / 400 VAC Ph-Ph (Three Phase)*
220 VAC Ph+N (Single Phase)*
- Output Voltage : 230 VAC Ph+N / 400 VAC Ph-Ph (Three Phase)*
110 VAC Ph+N (Single Phase)*
- Frequency : 50 - 60 Hz
- Windings : Aluminum or Copper
- Connections : Star, Delta, Zig-Zag
- Protection Class : Standard**
- Isolation Class : Standard***
Varnish Under Vacuum According to Isolation Class
- Cooling : Natural**
- Ambient Temperature : -10°C+40°C
- Storage Conditions : -20°C+70°C
- Connections : As Per to Customer Requirements:
All Types of Terminals and Lugs



* It can be produced in different voltages and powers as requested.

** Can be changed upon request.

*** Can be produced in H (180°C) class upon request.

3 PHASE ISOLATION TRANSFORMERS

Power	Chassis Dims. (WxHxD)	Chassis Weight	Connection	Wire
5kVA	630 x 715 x 332	70	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
10kVA	805 x 700 x 665	110	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
15kVA	650 x 459 x 564	120	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
20kVA	800 x 800 x 647	200	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
30kVA	800 x 800 x 647	240	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
40kVA	800 x 800 x 647	285	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
60kVA	905 x 1000 x 780	355	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
72kVA	905 x 1000 x 780	385	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
80kVA	905 x 1000 x 780	410	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
100kVA	905 x 1000 x 780	430	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
120kVA	905 x 1000 x 780	470	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
150kVA	905 x 1000 x 780	550	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
200kVA	1120 x 1000 x 842	690	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
250kVA	1120 x 1000 x 842	790	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
300kVA	1200 x 1100 x 800	900	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
450kVA	1200 x 1100 x 800	1100	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
500kVA	1200 x 1100 x 800	1280	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
720kVA	1285 x 1505 x 1070	1850	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
800kVA	1510 x 1690 x 1380	2100	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
1000kVA	1510 x 1690 x 1380	2500	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM
1200kVA	1510 x 1690 x 1380	2750	Y-Y/Δ-Y/Y-Δ/Δ-Δ	COPPER/ALUMINIUM

1 PHASE ISOLATION TRANSFORMERS

Power	Chassis Dims. (WxHxD)	Chassis Weight	Connection	Wire
1kVA	306 x 290 x 340	20	1 Phase	COPPER/ALUMINIUM
2kVA	306 x 290 x 340	24	1 Phase	COPPER/ALUMINIUM
5kVA	625 x 800 x 495	75	1 Phase	COPPER/ALUMINIUM
10kVA	625 x 800 x 495	105	1 Phase	COPPER/ALUMINIUM
15kVA	625 x 800 x 495	120	1 Phase	COPPER/ALUMINIUM
25kVA	600 x 700 x 638	180	1 Phase	COPPER/ALUMINIUM

Elektroiz reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Elektroiz products previously or subsequently sold. Elektroiz does not guarantee the items of the accuracy and completeness.